

# MATERIAL SAFETY DATA SHEET

**PRODUCT: VALENCA OLDE WORLD STUCCO**

**MANUFACTURED BY: A.W. COOK CEMENT PRODUCTS**

**242 Amy Industrial Lane  
Hoschton, Ga. 30548**

**EMERGENCY PHONE: 706-654-4706**

**INFORMATION PHONE: 706-654-3677**

## **SECTION I**

---

### N.F.P.A. & H.M.I.S. RATING

HAZARD INDEX

4= Severe  
3= Serious  
2= Moderate  
1= Slight  
0= Minimal

Health  
1

Flammability

Reactivity

Special

## **SECTION II**

---

HAZARDOUS COMPONENTS

..OSHA PEL..ACGIH TLV..OTHER LIMITS..PERCENT

Mineral Fillers	5 mg/m3	15 mg/m3	10-20
Free SiO2	10 mg/m3	5 mg/m3	2

None of the components of the mixture are considered Hazardous Material or carcinogens (1910.1200 Hazard Communication (d) (4))

TRANSPORTATION INFORMATION: NA

## **SECTION III**

---

PHYSICAL CHEMICAL CHARACTERISTICS

Boiling Point: not known to boil  
Vapor Pressure (mm Hg): NA  
Vapor Density (air=1): NA  
Solubility: Negligible  
Appearance: Powder

Specific Gravity (H2O=1): 2.2  
Melting Point: NA  
Evaporation (Butyl Acetate=1): NA

## **SECTION IV**

---

FIRE AND EXPLOSION HAZARD DATA

Flash Point: NA  
Flammable Limits: NA  
Extinguishing Media: NA

Special Fire Fighting Procedures: NA  
Unusual Fire & explosion Hazards: NA

## **SECTION V**

---

REACTIVITY DATA

Stability: Stable

Incompatibility (materials to avoid): None

Conditions to avoid: None  
Hazardous Polymerization: will not occur

Hazardous Decomposition (byproducts): None

## **SECTION VI**

---

### HEALTH HAZARD DATA

Routes of Entry: Inhalation? **Yes** Skin? No Ingestion? No  
Skin Contact: NA Eye Contact: NA Ingestion: NA  
Inhalation: Repeated inhalation of respirable dust for extended periods of time may cause injury to lungs.  
Carcinogenicity: NA NTP? No IARC Monographs? No OSHA Regulated? No

SIGNS & SYMPTOMS OF EXPOSURE: Repeated inhalation for extended periods of time may cause lung injury.(silicosis)

### EMERGENCY & FIRST AID PROCEDURES:

Skin: Wash thoroughly with soap and water.  
Eyes: Flush with water for 15 minutes. Call a physician.  
Inhalation: NA  
Ingestion: NA

## **SECTION VII**

---

### PRECAUTIONS FOR SAFE HANDLING & USE

Steps to be taken in case material is released or spilled: Avoid excessive dusting.  
Waste Disposal Method: Preferred procedure is to vacuum material. Otherwise; spray with water & clean with broom & shovel. Dispose of in accordance with local, state, and federal regulations.  
Precautions to be taken in handling & storing: Avoid dusty conditions.  
Other Precautions: Avoid prolonged contact between skin & wet or moist Portland cement. Skin areas that have been in contact with wet or moist Portland cement should be washed thoroughly with soap & water.

## **SECTION VIII**

---

### CONTROL MEASURES

Respiratory protection: NIOSH approved respiratory protection for dusty environment.  
Ventilation: Observe EPA standards.  
Protective gloves: For sensitive skin.  
Eye protection: Safety goggles or face shield to protect against accidental splashes.  
Other protective clothing & equipment: Safety Showers & eye wash stations should be available.  
Work/hygienic practices: Wash thoroughly with soap & water before eating, smoking or using washroom.  
Remove & wash contaminated clothing before re-use.

PREPARED BY: DAN COOK  
ORIGINAL DATE: 5-15-92

TITLE: PRESIDENT  
REVISED DATE: 8-5-09

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind, express or implied, and we assume no responsibility for any loss, damage, or expense, direct or consequential, arising out of their use.