

# ACRYLIC LIQUID

The logo for Cook Brand, featuring the word "Cook" in a large, white, serif font with a registered trademark symbol, and the word "BRAND" in a smaller, white, sans-serif font below it. The logo is set against a dark blue background with a white swoosh on the right side.

## MANUFACTURER

A.W. Cook Cement Products  
242 Amy Industrial Lane  
Hoschton, GA 30548  
Phone (706) 654-3677  
Fax (706) 654-3662

## DESCRIPTION

COOK BRAND ACRYLIC LIQUID is a ready to use, modified acrylic emulsion designed to permanently bond concrete, masonry, stucco, terrazzo and Portland cements and mixes to horizontal and vertical surfaces. Will not re-emulsify. ACRYLIC LIQUID is non-toxic, non-flammable, and safe to use. It is free of solvents or harmful ingredients, and is non-combustible. ACRYLIC LIQUID reinforced cements and mortars have greater adhesion, are more resistant to freeze-thaw cycling, the attacks of acids, alkalis or chemicals, and are more abrasion resistant than the concrete to which they bond.

## USES

ACRYLIC LIQUID is used to bond new concrete to either new or old concrete. For patching and resurfacing precast panels, industrial concrete floors, highway and bridge deck repairs. Use ACRYLIC LIQUID to mix FAST PATCH, CONCRETE PATCH, HYDROSEAL or sand/cement mixes to increase bond, compressive and flexural strength.

## APPLICATION

Remove all dirt, oil, curing compounds, sealers, paint or any other foreign material from The surface you wish to bond to. Per-mix sand cement mixes. Blend together one part water to one part ACRYLIC LIQUID. Add this blend to powder and mix thoroughly. Add additional liquid until proper consistency is obtained. BONDING SLURRY MIX: 1 part ACRYLIC LIQUID, 1 part water, 5 parts cement and 2.5 parts sand, Mix ingredients to a creamy, paste like consistency. Use a stiff bristle brush and scrub the slurry into the surface. Old concrete should be thoroughly moistened with water before applying slurry.

Any excess water should be removed by mopping to prevent puddling, Apply topping while slurry is still WET AND TACKY, DO NOT ALLOW TO DRY. THIS WILL RESULT IN BOND FAILURE.

For applications requiring a re-wettable bonding agent, use COOKBRAND BONDING AGENT. TOPPING MIXES: For topping mixes over 3/8" deep to 1 1/2" deep, use COOK BRAND CONCRETE PATCH "HIGH BUILD" for shallow patching and thin resurfacing of worn, broken or spalled concrete surfaces use COOK BRAND CONCRETE PATCH "REGULAR" kits.

## CLEAN UP

Clean up is simple and easy with soap and water. Rinse tools before material hardens.

## PRECAUTIONS

If in eye: flush immediately with water for 15 minutes. Consult a physician if irritation persists. If on skin: wash affected area with soap and water. Launder contaminated clothing before reuse. If vapors inhaled: remove subject to fresh air, In case of fire: this product is non-flammable in the liquid state. Use water spray, foam, dry chemical or carbon dioxide on dried product. Spill or leak: contain and remove with inert absorbent. Keep spill out of sewers.

## PACKAGING

1 gallon jugs 4/ case  
5 gallon pails 36/ pallet  
55 gallon Drums