



Liquid Additive “A”

MANUFACTURER

A.W. Cook Cement Products
242 Amy Industrial Lane
Hoschton, Ga. 30548
Phone (706) 654-3677
Fax (706) 654-3662

GENERAL USES

Blend liquid component A to powder component B in accordance with mixing instructions on component B. Liquid component A is used with Cemtec powdered Gel Patch, Trowel Patch and Screed Patch. This is the only liquid needed for the above products.

LIMITATIONS

Do not allow to freeze. If frozen, discard product. Ambient temperature must be 40° F or above during application and curing.

SHELF LIFE

12 Months in the original unopened container.

STORAGE

Store in a dry area away from direct sunlight. The product should be conditioned to between 40° F and 95° F before use. If frozen, the product must be discarded.

HEALTH PRECAUTIONS

The component B contains Portland cement and crystalline free silica. Avoid breathing dust. Exercise care, as with handling any chemical construction product.

SAFETY PRECAUTIONS

Use adequate ventilation. Use of a NIOSH/MSA approved dust respirator, safety goggles and chemical resistant gloves are strongly recommended. Remove contaminated clothing immediately.

FIRST AID

Skin contact: wash thoroughly with soap and water.
Eye contact: flush immediately with water and contact a physician.
Respiratory problems: remove affected person to fresh air immediately and contact a physician.
Hygiene: wash hands immediately after use. Wash clothing before reuse.

SPILLS

Collect in appropriate container. Uncured material may be removed with water.

DISPOSAL

Dispose of in accordance with local, state and federal regulations.

WARNING

Keep container closed when not in use. Keep out of reach of children. Not for internal consumption. For industrial use only by a qualified technician. Consult the Material Safety Data Sheet for further health and safety information.