



UNIVERSAL POLYMER CONCENTRATE

MANUFACTURER

A.W. Cook Cement Products
242 Amy Industrial Lane
Hoschton, GA. 30548
Phone (706) 654-3677
Fax (706) 654-3662

DESCRIPTION

CEMTEC UNIVERSAL POLYMER CONCENTRATE is a white liquid used in various CEMTEC products. It is a unique blend of polymers designed to be used as a bonding primer as well as the liquid additive portion of the 2 Part Broomed Overlay system, 2 Part Stamp Mix and 2 Part Spray Mix.

MIXING & USES

1) As a bonding primer for overlays and repair products:

- a) Make sure surface preparation guidelines are followed. These guidelines are spelled out on the product data sheets.
- b) After the substrate has been prepared and saturated with water, remove any puddles of water and apply UNIVERSAL POLYMER CONCENTRATE mixed 1 to 1 with water. Scrub the polymer into the surface with a medium to stiff bristle broom. Make sure all areas are covered. Leaving no puddles. Allow the polymer to dry to a clear film. Spiked shoes or golf shoes should be worn when walking on the primed surface so as not to pull up any cured polymer. Proceed with the application according to instructions on the data sheets.

PACKAGING

- 5 gallon plastic pails
- 55 gallon drums

COVERAGE

Bonding Primer - 200 sq. ft. per gallon.

PRECAUTIONS

Do Not allow UNIVERSAL POLYMER CONCENTRATE to freeze.

Adding more water than recommended when diluting will negate any guarantees and will be extremely detrimental to the performance of the finished product.

Do Not allow placed material to freeze for 48 hours.

TECHNICAL DATA

TYPE I / RE-EMULSIFIABLE
ASTM C-1059-86

Bond Strength 490 psi